

Diagonal 39.7 mm (Type 2.5) CMOS solid-state Image Sensor with Square Pixel for Color Cameras

Description

The IMX947-AQB is diagonal 39.7 mm (Type 2.5) CMOS active pixel type solid-state image sensor with a square pixel array and 26.37 M effective pixels. This chip features a global shutter with variable charge-integration time. This sensor operates with 3.3 V, 2.9 V, 1.1 V, and 1.8 V quadruple power supply. High sensitivity and low dark current characteristics are achieved.

(Applications: FA cameras, 3D vision cameras)

Features

- ◆ CMOS active pixel type dots
- ◆ Built-in timing adjustment circuit, H/V driver and serial communication circuit
- ◆ Global shutter function
- ◆ Input clock frequency 37.125 MHz / 74.25 MHz
- ◆ Number of recommended recording pixels: 5120 (H) × 5120 (V) approx. 26.21 M pixels
- ◆ Readout mode
 - All-pixel scan mode, ROI mode, Vertical / Horizontal - Normal / Inverted readout mode
- ◆ Readout rate (*) At high frame rates, control so as not to exceed $T_j = +85\text{ }^\circ\text{C}$
 - Maximum frame rate in All-pixel scan mode: *controller mode
 - 8-bit 423.4 frame/s, 10-bit 383.2 frame/s, 12-bit 277.7 frame/s
- ◆ Variable-shutter speed
- ◆ Pulse Output Function
 - The monitor output for Integration period (TOUT0) and for internal AD period (TOUT1)
- ◆ 8-bit / 10-bit / 12-bit Output
- ◆ CDS / PGC function
 - 0 dB to 24 dB: Variable analog Gain (0.3 dB step)* 12-bit
 - 24.3 dB to 48 dB: Fixed analog Gain: 24 dB + variable digital Gain: 0.3 dB to 24 dB (0.3 dB step)*12-bit
 - 0 dB to 18 dB: Variable analog Gain (0.3 dB step)* 8-bit / 10-bit
 - 18.3 dB to 42 dB: Fixed analog Gain: 18 dB + variable digital Gain: 0.3 dB to 24 dB (0.3 dB step)*8-bit / 10-bit
- ◆ I/O interface
 - SLVS-EC (2 Lane , 4 Lane , 6 Lane , 8 Lane , 4 Lane × 2 , 6 Lane × 2 , 8 Lane × 2) output
 - SLVS-EC Baud Rate: 4.752 Gbps / lane 9.504 Gbps / lane 12.474 Gbps / lane (Grade 3, 4 and 5)
- ◆ CRA characteristics
 - The target CRA is 6 degree at 100% image height.
- ◆ Ceramic package with connector. The connector is floating type.
- ◆ Seal glass: both sides are processed by AR coating

Pregius S

* Pregius S and its logo are registered trademarks or trademarks of Sony Group Corporation or its affiliates. Pregius S is a global shutter sensor technology for active pixel-type CMOS image sensors. By stacking the signal processing on the back illuminated type CMOS Image Sensor it realizes small chip size and high sensitivity, whilst using the high picture quality global shutter pixel technology of Pregius.

Device Structure

◆ CMOS image sensor		
◆ Image size	Diagonal 39.7 mm (Type 2.5)	Approx. 26.37 M pixels
◆ Total number of pixels	5136 (H) × 5184 (V)	Approx. 26.62 M pixels
◆ Number of effective pixels	5136 (H) × 5136 (V)	Approx. 26.37 M pixels
◆ Number of active pixels	5124 (H) × 5124 (V)	Approx. 26.25 M pixels
◆ Number of recommended recording pixels	5120 (H) × 5120 (V)	Approx. 26.21 M pixels
◆ Unit cell size	5.48 μm (H) × 5.48 μm (V)	
◆ Optical black	Horizontal (H) direction: Front 0 pixel, Rear 0 pixel Vertical (V) direction: Front 32 pixels, Rear 0 pixel	
◆ Package	Ceramic package with connector 160 pin × 2	45 mm (H) × 52 mm (V)

Image Sensor Characteristics

(Tj = 60 °C)

Item		Value	Remarks
Sensitivity	Typ.	TBD	-
Saturation signal	Min.	TBD	-

Basic Drive Mode

Drive mode	Recommended number of recording pixels	Maximum frame rate [frame/s]	Output interface	Output [bit]
All-pixel (Controller mode)	5120 (H) × 5120 (V) approx. 26.21 M pixels	414.3	SLVS-EC 6 × 2 Lane	8
		350.4		10
		277.7		12

Note: All frame rates are tentative.

Sony Semiconductor Solutions Corporation reserves the right to change products and specifications without prior notice. "Sony", "SONY" logo are registered trademarks or trademarks of Sony Group Corporation or its affiliates.

